



Industrial  
Lubricants



Automotive  
Lubricants



Biodegradable  
Lubricants



Agricultural  
Lubricants



Cleaning &  
Maintenance



Greases &  
Pastes



Foodsafe  
Lubricants



Heritage Oils



Lubrication  
Equipment



Metalworking  
Fluids



## ATF Dexron II

Automatic Transmission & Power Steering Fluid  
Product Code: A30

### Product Description

Formulated from high viscosity index base oils, Pennine ATF Dexron II contains the additives to exceed the requirements of the G M -Dexron II specification. It provides good lubrication of gears and bearings and deposit free control valves and actuating mechanisms. Minimum power loss and consistent performance are ensured for the life of the fluid.

### Applications

Pennine ATF Dexron II is recommended for use in automatic transmissions and torque converters of General Motors and other manufacturers specifying this type of fluid. It is suitable for both commercial vehicles and passenger car applications, as well as the majority of power steering systems.

### Performance Specifications

Pennine ATF Dexron II meets the performance requirements of General Motors Dexron II, Mercedes Benz and Detroit Allison C-3.

### Typical Test Data

Density @ 60°F	0.87
K. V. @ 40°C cSt	37.5
K. V. @ 100°C cSt	73
Viscosity Index	164
Flash Point ( IP35) °C	180



Certificate Number: 9480  
ISO 9001




Pennine Lubricants Limited Company reg no. 3510091



32 Atlas Way,  
Sheffield, S4 7QQ

T. 0114 285 2987  
E. [info@penninelubricants.co.uk](mailto:info@penninelubricants.co.uk)  
W. [www.penninelubricants.co.uk](http://www.penninelubricants.co.uk)

Industrial  
LubricantsAutomotive  
LubricantsBiodegradable  
LubricantsAgricultural  
LubricantsCleaning &  
MaintenanceGreases &  
PastesFoodsafe  
Lubricants

Heritage Oils

Lubrication  
EquipmentMetalworking  
Fluids

## ATF Dexron II

Automatic Transmission & Power Steering Fluid  
Product Code: A30

### Availability

Pennine ATF Dexron II is available in bulk, 1000L IBC's, 205 litre barrels, 25 litre, 5 litre and 1 litre bottles.

### Storage

Barrels of lubricant should always be stored in such a way that will prevent the ingress of water when stored in the open.

### Health & Safety

Please refer to the relevant Health and Safety Data Sheet, a copy of which is freely available to all our customers.

Data represented is typical of that obtained with normal production tolerances and does not constitute a specification. The policy of Pennine Lubricants is one of continual improvement, we therefore reserve the right to change specification without notice.

Certificate Number: 9480  
ISO 9001

Pennine Lubricants Limited Company reg no. 3510091

32 Atlas Way,  
Sheffield, S4 7QQT. 0114 285 2987  
E. [info@penninelubricants.co.uk](mailto:info@penninelubricants.co.uk)  
W. [www.penninelubricants.co.uk](http://www.penninelubricants.co.uk)