


Industrial
Lubricants



Automotive
Lubricants



Biodegradable
Lubricants




Agricultural
Lubricants



Cleaning &
Maintenance




Greases &
Pastes




Foodsafe
Lubricants



Heritage Oils



Lubrication
Equipment



Metalworking
Fluids



Chainsaw Oils

Premium Quality "Anti-Fling" Lubricants
Product Code: A61, A62, A63

Product Description

Pennine Chainsaw Oils have been formulated for use in different types of chainsaws for the lubrication of parts subject to violent movement. These include a special tacky additive to provide non-throw characteristics when lubricating chainsaw cutter bars and chains.

Applications

Light Chainsaw Oil is a "tacky" low viscosity oil for use in pressure fed chains while Medium and Heavy Chainsaw Oils are very viscous oils for bars and chains on pump fed chain saws.

Typical Test Data

Chainsaw Oil	A61 Light	A62 Medium	A63 Heavy
Density @ 20°C	0.89	0.89	0.89
K. V. @ 40°C (cSt)	68	100	220
K. V. @ 100°C (cSt)	8.8	11.4	21.4
Viscosity Index	100	100	108
Flash Point (°C)	234	245	260
Pour Point (°C)	-22	-10	-10

Availability

Pennine Chainsaw Oils are available in bulk, 1000 litre IBCs, 205 litre barrels, 25 litre drums, 5 litre and 1 litre bottles.

Storage

Barrels of lubricant should always be stored in such a way that will prevent the ingress of water when stored in the open.

Health & Safety

Please refer to the relevant Health and Safety Data Sheet, a copy of which is freely available to all our customers.

Data represented is typical of that obtained with normal production tolerances and does not constitute a specification. The policy of Pennine Lubricants is one of continual improvement, we therefore reserve the right to change specifications without notice.



Certificate Number: 9480
ISO 9001



Pennine Lubricants Limited Company reg no. 3510091



32 Atlas Way,
Sheffield, S4 7QQ

T. 0114 285 2987
E. info@penninelubricants.co.uk
W. www.penninelubricants.co.uk