


Industrial  
Lubricants



Automotive  
Lubricants



Biodegradable  
Lubricants



Agricultural  
Lubricants



Cleaning &  
Maintenance




Greases &  
Pastes




Foodsafe  
Lubricants



Heritage Oils



Lubrication  
Equipment



Metalworking  
Fluids



## Flushing Oil

High Quality Mineral Flushing Oil  
Product Code: A3F

### Product Description

Pennine Flushing Oil is developed to provide for the efficient removal of debris and deposits, which might be retained in the system after oil drain, thus greatly reducing the build-up of deposits.

### Applications

Used for the removal of gums and lacquers caused by the oxidation of oils subjected to high operating temperatures and other environmental problems of dust, water, etc.

### Typical Test Data

ISO Viscosity	32
Density @ 20° C	0.87
K.V. @ 40° C cSt	31
K.V. @ 100° C cSt	5.3
Viscosity Index	101
Flash point ° C	226
Pour Point ° C	-22

### Availability

Pennine Flushing Oil is available in bulk, 1000 litre IBC's, 205 litre barrels, 25 litre drums and 5 litre plastic bottles.

### Storage

Barrels of lubricant should always be stored in such a way that will prevent the ingress of water when stored in the open.

### Health & Safety

Please refer to the relevant Health and Safety Data Sheet, a copy of which is freely available to all our customers.

Data represented is typical of that obtained with normal production tolerances and does not constitute a specification. The policy of Pennine Lubricants is one of continual improvement, we therefore reserve the right to change specifications without notice.



Certificate Number: 9480  
ISO 9001



Pennine Lubricants Limited Company reg no. 3510091



32 Atlas Way,  
Sheffield, S4 7QQ

T. 0114 285 2987  
E. [info@penninelubricants.co.uk](mailto:info@penninelubricants.co.uk)  
W. [www.penninelubricants.co.uk](http://www.penninelubricants.co.uk)