



Industrial  
Lubricants



Automotive  
Lubricants



Biodegradable  
Lubricants



Agricultural  
Lubricants



Cleaning &  
Maintenance



Greases &  
Pastes



Foodsafe  
Lubricants



Heritage Oils



Lubrication  
Equipment



Metalworking  
Fluids



## Gear Oils SAE

Straight Non EP Gear Oils

Product Code: A20, A2E

### Product Description

Pennine Gear Oil SAE 90 and SAE 80 are manufactured from selected solvent refined base stocks and is non-additive treated to meet the API GL1 service classification.

### Applications

These products are recommended for use in automotive spiral bevel, and worm gear axle units where EP Oils are not considered either necessary, or in some instances, desirable.

### Performance Specifications

Meets the Requirements of API service classification GL1.

### Typical Test Data

	A20	A2E
SAE classification	90	80
K. V. @ 100° C (cSt)	17.0	10.2
K. V. @ 40° C (cSt)	189	80
Viscosity Index	96	96
Density @ 15° C	0.89	0.88
Flash Point (°C)	245	205
Pour Point (°C)	-9	-18

### Availability

Pennine Gear Oil SAE 90 is available in bulk, 205 litre barrels, 25 litre drums and 10 litre, 5 litre, 1 litre and 500ml plastic bottles.

### Storage

Barrels of lubricant should always be stored in such a way that will prevent the ingress of water when stored in the open.

### Health and Safety

Please refer to the relevant Health and Safety Data Sheet, a copy of which is freely available to all our customers.

Data represented is typical of that obtained with normal production tolerances and does not constitute a specification. The policy of Pennine Lubricants is one of continual improvement, we therefore reserve the right to change specifications without notice.

