



Industrial
Lubricants



Automotive
Lubricants



Biodegradable
Lubricants



Agricultural
Lubricants



Cleaning &
Maintenance



Greases &
Pastes



Foodsafe
Lubricants



Heritage Oils



Lubrication
Equipment



Metalworking
Fluids



Limited Slip LS

Limited Slip Differential Lubricants

Product Code: A29, A2D

Product Description

Pennine Limited Slip LS 90 and LS 140 are extreme pressure gear oils treated with a friction modifier additive and are recommended for use in limited slip differentials.

Applications

Recommended for use in limited slip differentials.

Performance Specifications

Meet the performance requirements of MIL-L-2105D and API GL5.

Typical Test Data

CODE	A29	A2D
SAE	90	140
Specific Gravity @ 20 ^o C	0.9	0.91
K.V. @ 40 ^o C cSt	180	430
K.V. @ 100 ^o C cSt	16	30
Viscosity Index	98	100
Flash point (IP35) ^o C	230	270
Pour Point (IP15) ^o C	-45	-20

Availability

Pennine Limited Slip LS Gear Oils are available in bulk, 1000 litre IBC's, 205 litre barrels, 25 litre drums and 5 litre plastic bottles.

Storage

Barrels of lubricant should always be stored in such a way that will prevent the ingress of water when stored in the open.

Health and Safety

Please refer to the relevant Health and Safety Data Sheet, a copy of which is freely available to all our customers.

Data represented is typical of that obtained with normal production tolerances and does not constitute a specification. The policy of Pennine Lubricants is one of continual improvement, we therefore reserve the right to change specifications without notice.

