



Industrial  
Lubricants



Automotive  
Lubricants



Biodegradable  
Lubricants



Agricultural  
Lubricants



Cleaning &  
Maintenance



Greases &  
Pastes



Foodsafe  
Lubricants



Heritage Oils



Lubrication  
Equipment



Metalworking  
Fluids



## Limited Slip LS

Limited Slip Differential Lubricants  
Product Code: A29, A2D

### Product Description

Pennine Limited Slip LS 90 and LS 140 are extreme pressure gear oils treated with a friction modifier additive and are recommended for use in limited slip differentials.

### Applications

Recommended for use in limited slip differentials.

### Performance Specifications

Meet the performance requirements of MIL-L-2105D and API GL5.

### Typical Test Data

CODE	A29	A2D
SAE	90	140
Specific Gravity @ 20°C	0.9	0.91
K.V. @ 40°C cSt	180	430
K.V. @ 100°C cSt	16	30
Viscosity Index	98	100
Flash point (IP35) °C	230	270
Pour Point (IP15) °C	-45	-20

### Availability

Pennine Limited Slip LS Gear Oils are available in bulk, 1000 litre IBC's, 205 litre barrels, 25 litre drums and 5 litre plastic bottles.

### Storage

Barrels of lubricant should always be stored in such a way that will prevent the ingress of water when stored in the open.

### Health & Safety

Please refer to the relevant Health and Safety Data Sheet, a copy of which is freely available to all our customers.

Data represented is typical of that obtained with normal production tolerances and does not constitute a specification. The policy of Pennine Lubricants is one of continual improvement, we therefore reserve the right to change specifications without notice.



Certificate Number: 9480  
ISO 9001



Pennine Lubricants Limited Company reg no. 3510091



32 Atlas Way,  
Sheffield, S4 7QQ

T. 0114 285 2987  
E. [info@penninelubricants.co.uk](mailto:info@penninelubricants.co.uk)  
W. [www.penninelubricants.co.uk](http://www.penninelubricants.co.uk)