



Industrial
Lubricants



Automotive
Lubricants



Biodegradable
Lubricants



Agricultural
Lubricants



Cleaning &
Maintenance



Greases &
Pastes



Foodsafe
Lubricants



Heritage Oils



Lubrication
Equipment



Metalworking
Fluids



Multisol G

Semi Synthetic Machining & Grinding Coolant
Product Code: AGC

Product Description

Pennine Multisol G is a medium oil content, high dilution, semi synthetic soluble cutting fluid. When mixed with water it forms a biostable emulsion that is highly resistant to bacterial and fungal degradation giving freedom from bad smells and slimy deposits. It is a low odour, non-phenolic, nitrite free product based on solvent refined mineral oils giving a translucent green emulsion.

Applications

Multisol G is recommended for general machine shop operations including CNC machines where extended tool life and a translucent product are desirable. It is suitable for use with most materials including medium tensile steels, aluminium and its alloys and yellow metals.

Features & Benefits

- Translucent emulsion ~ Good workpiece visibility
- Highly biostable ~ Extended sump life / fewer fluid changes
- Multi metal compatibility ~ Allows for grade rationalisation
- Excellent corrosion protection ~ Protects machines & workpieces
- Chlorine free ~ Reduced disposal costs

Typical Test Data

Characteristic / Test	Data
Appearance (concentrate)	Fluorescent Green
Appearance (emulsion)	Translucent Green
Specific Gravity @ 15°C	1.01
pH @ 5%	9.3
IP 287 Breakpoint Corrosion	1.5 %
IP 125 Herbert Corrosion Test	1.11%
Dilution Range (min ~ max)	3 ~ 8 %
Refractometer Conversion Factor	1.26
Water Hardness Range ppm CaCO ₃ (min ~ max)	50 ~ 300

Actual dilution rates may vary depending on application. Please consult with Technical Services to determine the most suitable dilution for your application.



Certificate Number: 9480
ISO 9001



Pennine Lubricants Limited Company reg no. 3510091



32 Atlas Way,
Sheffield, S4 7QQ

T. 0114 285 2987
E. info@penninelubricants.co.uk
W. www.penninelubricants.co.uk



PENNINE

LUBRICANTS

PRODUCT DATA

Revision Date 09/16jg
Page 2 of 2



Industrial
Lubricants



Automotive
Lubricants



Biodegradable
Lubricants



Agricultural
Lubricants



Cleaning &
Maintenance



Greases &
Pastes



Foodsafe
Lubricants



Heritage Oils



Lubrication
Equipment



Metalworking
Fluids



Multisol G

Semi Synthetic Machining & Grinding Coolant
Product Code: AGC

Coolant Care

To promote maximum service life, it is strongly advised that coolant systems are thoroughly sterilised with Bioflush System Cleaner prior to coolant changes (see Bioflush Technical Data Sheet for further information and guidelines).

To maintain the efficiency of the coolant, daily checks for concentration with a hand refractometer is recommended. Maintaining a consistent concentration is paramount to prolonging the fluid sump life. Further tests for bacteria, fungus, pH and tramp oil contamination are available through our PROCARE Fluid Management Service and helps users to comply with current HSE legislative requirements. Please contact us for further details.

Availability & Storage

Pennine Multisol G is available in 1000 litre IBC's, 205 litre barrels, 25 litre drums and 5 litre plastic bottles.

Barrels of lubricant should always be stored in such a way that will prevent the ingress of water when stored in the open. Protect from frost.

Health & Safety

Please refer to the relevant Safety Data Sheet, a copy of which is freely available to all our customers.

Data represented is typical of that obtained with normal production tolerances and does not constitute a specification. The policy of Pennine Lubricants is one of continual improvement; we therefore reserve the right to change specifications without notice.



Certificate Number: 9480
ISO 9001



Pennine Lubricants Limited Company reg no. 3510091



32 Atlas Way,
Sheffield, S4 7QQ

T. 0114 285 2987
E. info@penninelubricants.co.uk
W. www.penninelubricants.co.uk