



Industrial
Lubricants



Automotive
Lubricants



Biodegradable
Lubricants



Agricultural
Lubricants



Cleaning &
Maintenance



Greases &
Pastes



Foodsafe
Lubricants



Heritage Oils



Lubrication
Equipment



Metalworking
Fluids



Universal 2-Stroke Oil

Mineral Self Mix 2-Stroke Engine Oil

Product Code: A53

Product Description

Pennine Universal 2 Stroke Oil provides excellent deposit and wear control for air cooled two stroke engines requiring lubricants meeting API TC and JASO FB quality. It is also suitable for water cooled two stroke engines not prone to pre-ignition.

Applications

Recommended for use in air cooled stand-by generators, chain saws, lawn mowers and other 2 stroke engine and machinery where this type of oil is recommended. Non agricultural uses include motorcycles, mopeds, scooters and small outboard motors.

Performance Specifications

Meets the following performance specifications where applicable:

ISO: EGB JASO: FB API: TC

Typical Test Data

Density @ 20 ^o C	0.89
K. V. @ 40 ^o C cSt	110
K. V @ 100 ^o C cSt	12.8
Viscosity Index	100
Flash point ^o C	245
Pour Point ^o C	-10

Availability

Pennine Universal 2 Stroke Oil is available in 1000 litre IBC's, 205 litre barrels, 25 litre drums, 5 litre, 1 litre and 100 ml plastic bottles.

Storage

Barrels of lubricant should always be stored in such a way that will prevent the ingress of water when stored in the open.

Health and Safety

Please refer to the relevant Health and Safety Data Sheet, a copy of which is freely available to all our customers.

Data represented is typical of that obtained with normal production tolerances and does not constitute a specification. The policy of Pennine Lubricants is one of continual improvement, we therefore reserve the right to change specifications without notice.

