

**Section 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier****Product name:** UNIVERSAL TWO STROKE OIL**Product code:** A53**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of substance / mixture:** Lubricating oil for Two Stroke Engines**1.3. Details of the supplier of the safety data sheet****Company name:** Pennine Lubricants Limited  
Unit 35 Limestone Cottage Lane  
Sheffield  
South Yorkshire  
S6 1NJ  
United Kingdom**Tel:** 0114 285 2987**Fax:** 0114 285 2988**Email:** info@penninelubes.plus.com**1.4. Emergency telephone number****Emergency tel:** 0114 285 2987 (Office hours only)**Section 2: Hazards identification****2.1. Classification of the substance or mixture****Classification under CLP:** This product has no classification under CLP.**2.2. Label elements****Label elements:** This product has no label elements.**2.3. Other hazards****PBT:** This product is not identified as a PBT/vPvB substance.**Section 3: Composition/information on ingredients****3.2. Mixtures****Hazardous ingredients:**

**SAFETY DATA SHEET**  
UNIVERSAL TWO STROKE OIL

Page: 2

LOW ODOUR KEROSENE - REACH registered number(s): 01-2119456620-43

EINECS	CAS	PBT / WEL	CLP Classification	Percent
926-141-6	-	-	Asp. Tox. 1: H304	1-10%

#### Section 4: First aid measures

##### 4.1. Description of first aid measures

**Skin contact:** Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes.

**Ingestion:** Wash out mouth with water.

**Inhalation:** Consult a doctor.

##### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be irritation of the throat.

**Inhalation:** No symptoms.

##### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Not applicable.

#### Section 5: Fire-fighting measures

##### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

##### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

##### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

#### Section 6: Accidental release measures

##### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Spillages may be slippery. Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up to prevent the escape of liquid.

##### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

##### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

[cont...]

**SAFETY DATA SHEET**  
UNIVERSAL TWO STROKE OIL

Page: 3

**6.4. Reference to other sections**

**Reference to other sections:** Refer to section 8 of SDS.

**Section 7: Handling and storage**

**7.1. Precautions for safe handling**

**7.2. Conditions for safe storage, including any incompatibilities**

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed.

**7.3. Specific end use(s)**

**Specific end use(s):** No data available.

**Section 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Hazardous ingredients:**

**LOW ODOUR KEROSENE**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
EU	1200mg/m <sup>3</sup>	-	-	-

**DNEL/PNEC Values**

**DNEL / PNEC** No data available.

**8.2. Exposure controls**

**Engineering measures:** The floor of the storage room must be impermeable to prevent the escape of liquids.

**Respiratory protection:** Respiratory protection not required.

**Hand protection:** Protective gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

**Section 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

**State:** Liquid

**Colour:** Blue

**Odour:** Characteristic odour

**Evaporation rate:** Slow

**Solubility in water:** Insoluble

**Viscosity:** Viscous

**Kinematic viscosity:** 70

**Viscosity test method:** Kinematic Viscosity at 40C (cSt)

[cont...]

**SAFETY DATA SHEET**  
UNIVERSAL TWO STROKE OIL

Page: 4

**Boiling point/range°C:** >176

**Flash point°C:** >93

**Relative density:** 0.88

**9.2. Other information**

**Other information:** No data available.

**Section 10: Stability and reactivity**

**10.1. Reactivity**

**Reactivity:** Stable under recommended transport or storage conditions.

**10.2. Chemical stability**

**Chemical stability:** Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

**10.4. Conditions to avoid**

**Conditions to avoid:** Heat.

**10.5. Incompatible materials**

**Materials to avoid:** Strong oxidising agents. Strong acids.

**10.6. Hazardous decomposition products**

**Haz. decomp. products:** In combustion emits toxic fumes.

**Section 11: Toxicological information**

**11.1. Information on toxicological effects**

**Hazardous ingredients:**

**LOW ODOUR KEROSENE**

ORAL	RAT	LD50	>5000	mg/kg
------	-----	------	-------	-------

**Toxicity values:** No data available.

**Symptoms / routes of exposure**

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be irritation of the throat.

**Inhalation:** No symptoms.

**Section 12: Ecological information**

**12.1. Toxicity**

[cont...]

**SAFETY DATA SHEET**  
UNIVERSAL TWO STROKE OIL

Page: 5

**Hazardous ingredients:**

**LOW ODOUR KEROSENE**

RAINBOW TROUT ( <i>Oncorhynchus mykiss</i> )	96H LC50	>1000	mg/l
--	----------	-------	------

**12.2. Persistence and degradability**

**Persistence and degradability:** Inherently biodegradable

**12.3. Bioaccumulative potential**

**Bioaccumulative potential:** No bioaccumulation potential.

**12.4. Mobility in soil**

**Mobility:** Readily absorbed into soil.

**12.5. Results of PBT and vPvB assessment**

**PBT identification:** This product is not identified as a PBT/vPvB substance.

**12.6. Other adverse effects**

**Other adverse effects:** No data available.

**Section 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**Section 14: Transport information**

**Transport class:** This product does not require a classification for transport.

**Section 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Specific regulations:** Not applicable.

**15.2. Chemical Safety Assessment**

**Section 16: Other information**

**Other information**

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** H304: May be fatal if swallowed and enters airways.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

[final page]