



Industrial
Lubricants



Automotive
Lubricants



Biodegradable
Lubricants



Agricultural
Lubricants



Cleaning &
Maintenance



Greases &
Pastes



Foodsafe
Lubricants



Heritage Oils



Lubrication
Equipment



Metalworking
Fluids



Synthetic Gear Oil W

Synthetic Worm Gear Lubricant

Product Code: A27

Product Description

Pennine Synthetic Oil W is a synthetic automotive worm gear lubricant. It has high load carrying capacity and a low coefficient of friction, giving virtually no thickening in service and allowing oil change intervals 3 or 4 times longer than conventional worm gear oils.

Applications

Suitable for Foden worm drive axles and a variety of worm gears where longer oil change periods are required.

Pennine Synthetic Gear Oil W should not be mixed with any other oil.

Performance Specifications

Meets the requirement of Foden for their worm drive axles.

Typical Test Data

Specific Gravity @ 15.6°C (IP60)	1.02
K.V. @ 40°C cSt	130
K.V. @ 100°C cSt	22.25
Viscosity Index	200
Flash point (IP35) °C	318
Pour Point (IP15) °C	-28

Availability

Pennine Synthetic Gear Oil W is available in bulk, 1000 litre IBC's, 205 litre barrels, 25 litre drums and 5 litre plastic bottles.

Storage

Barrels of lubricant should always be stored in such a way that will prevent the ingress of water when stored in the open.

Health and Safety

Please refer to the relevant Health and Safety Data Sheet, a copy of which is freely available to all our customers.

Data represented is typical of that obtained with normal production tolerances and does not constitute a specification. The policy of Pennine Lubricants is one of continual improvement, we therefore reserve the right to change specifications without notice.



Certificate Number: 9480
ISO 9001



Pennine Lubricants Limited Company reg no. 3510091



32 Atlas Way,
Sheffield, S4 7QQ

T. 0114 285 2987

E. info@penninelubricants.co.uk

W. www.penninelubricants.co.uk