



Cleaning & Maintenance

Fleetwash CSW

Hybrid TFR/Snow Foam

Product Description

Fleetwash CSW is a hybrid of traffic film remover and snow foam. Fleetwash CSW has the cleaning performance of a traditional traffic film remover whilst having the adhesion of a snow foam when used through foaming equipment.

A low-cost product, that doesn't compromise on performance – Fleetwash CSW is the perfect alternative to a standard snow foam when cost is a factor!

Features & Benefits

- Versatile product ~ Safe to use on most vehicles
- Solvency characteristics ~ Increases cleaning efficiency
- Medium foam coverage ~ Less time rinsing
- Custom dilutable ~ Economical in use

Applications

Recommended Dilution

| Pre Spray | Pressure Washer/Steam Cleaner | Manual Brush/Sponge |
|------------|-------------------------------|---------------------|
| 5:1 – 10:1 | 20:1 – 30:1 | 20:1 – 30:1 |

Pre-wash vehicle with cold water to remove any heavy debris. Do not apply to hot bodywork - always soak the vehicle to cool the surfaces in hot weather with clean water.

Apply Fleetwash CSW to vehicle (see recommended dilution above). Start application at the bottom of the vehicle and work up. Agitate product with vehicle brush.

Rinse thoroughly after use with clean water.

See website for more information.

Typical Test Data

| | |
|----------------|--------------|
| Appearance | Liquid |
| Colour | Light Yellow |
| Odour | Mild |
| Density @ 20°C | 1.08 |
| pH | < 12 |



Certificate Number: 9480 ISO 9001



Sheffield Office:
32 Atlas Way, Sheffield, S4 7QQ
T. 0114 285 2987

Hinckley Office:
1 Maizefield, Hinckley, LE10 1YF
T. 01455 890 977

E. info@penninelubricants.co.uk

W. www.penninelubricants.co.uk

D2 Pro Range is owned by Pennine Lubricants Ltd. Company reg no. [3530091](#)



Cleaning & Maintenance

Availability

Fleetwash CSW is available in IBC (1000 litre), 205 litre barrels and 25 litre drums.

Storage

Fleetwash CSW should always be stored indoors and protected from extremes of temperature. Do not allow to freeze.

Health & Safety

Please refer to the relevant Safety Data Sheet, a copy of which is freely available to all our customers.

Data represented is typical of that obtained with normal production tolerances and does not constitute a specification. The policy of Pennine Lubricants is one of continual improvement, we therefore reserve the right to change specifications without notice.



Certificate Number: 9480 ISO 9001



Sheffield Office:
32 Atlas Way, Sheffield, S4 7QQ
T. 0114 285 2987

Hinckley Office:
1 Maizefield, Hinckley, LE10 1YF
T. 01455 890 977

E. Info@penninelubricants.co.uk

W. www.penninelubricants.co.uk

D2 Pro Range is owned by Pennine Lubricants Ltd. Company reg no. [3510091](#)