



Industrial Lubricants



Automotive Lubricants



Biodegradable Lubricants



Agricultural Lubricants



Cleaning & Maintenance



Greases & Pastes



Foodsafe Lubricants



Heritage Oils



Lubrication Equipment



Metalworking Fluids



Microcore M12

Dewatering Fluid & Medium Term Corrosion Preventative

Product Code: ADH

Product Description

Pennine Microcore M12 is a solvent based dewatering fluid and medium term rust preventative. The product offers excellent dewatering properties to displace water on contact before the solvent carrier evaporates leaving a thin greasy protective film.

Applications

Pennine Microcore M12 is designed to offer medium term corrosion protection of components making it ideal for intermediate storage or transportation periods of up to 12 months. The product can be applied by spraying or brushing. To ensure maximum dewatering and protection properties, components should be immersed into a suitable dip tank and then allowed to drain.

When not in use the product container must be resealed to prevent the solvent base evaporating off.

Typical Test Data

Microcore M12	
Density @ 15°C	0.82
% Residue	10
Flash Point (°C)	65
Film Thickness (Microns)	5
Indoor Protection	12 Months
Covered Outdoor Protection	2 Months

Availability

Pennine Microcore M12 is available in 1000 litre IBC's, 205 litre barrels, 25 litre drums and 5 litre tins.

Storage

Barrels of lubricant should always be stored in such a way that will prevent the ingress of water when stored in the open. Agitate before use.





Industrial
Lubricants



Automotive
Lubricants



Biodegradable
Lubricants



Agricultural
Lubricants



Cleaning &
Maintenance



Greases &
Pastes



Foodsafe
Lubricants



Heritage Oils



Lubrication
Equipment



Metalworking
Fluids



Microcore M12

Dewatering Fluid & Medium Term Corrosion Preventative
Product Code: ADH

Health and Safety

Please refer to the relevant Health and Safety Data Sheet, a copy of which is freely available to all our customers.

Data represented is typical of that obtained with normal production tolerances and does not constitute a specification. The policy of Pennine Lubricants is one of continual improvement, we therefore reserve the right to change specifications without notice.

