

#### **PRODUCT DATA**

Revision Date 07/20jg Page 1 of 2























## Eurosyn MAX FE 5w/30

Fuel Efficient Low SAPS Full Synthetic Diesel Engine Oil Product Code: AOK

## **Product Description**

Pennine Eurosyn MAX FE 5w/30 is a high performance, full synthetic, low SAPS heavy duty diesel engine oil. The product utilises a blend of full synthetic severely hydrotreated base stock, viscosity index improver, pour point depressant and a powerful state of the art performance system offering the user ultimate engine protection even under the most severe operating conditions.

## **Applications**

Eurosyn MAX FE 5w/30 is recommended for use where there is a requirement to meet the latest low emission requirements in particular Euro 6 applications. The product is suitable for extended drain intervals as defined by the manufacturer.

## **Performance Specification**

Eurosyn MAX FE 5w/30 meets the performance requirements of the following: -

ACEA E6, E9,E4,E7 API CJ-4, Cl-4, CH-4 Mercedes Benz MB 228.51 Volvo VDS-4 Scania LDF-4 IVECO TLS E6

Cummins CES 20081 DAF Renault Trucks RLD-3

Mack EO-O Premium Plus MAN M3477, M3677, M3271-1

**Typical Test Data** 

SAE Classification	5W/30
K. V.@ 40°C cSt	72.5
K. V. @ 100°C cSt	12.2
Viscosity Index	166
Flash Point <sup>O</sup> C	223
Density @ 15°C	0.861

#### **Availability**

Pennine Eurosyn MAX FE 5w/30 is available in bulk, 1000 litre IBC's, 205 litre barrels, 25 litre drums and 5 litre plastic bottles.

#### Storage

Barrels of lubricant should always be stored in such a way that will prevent the ingress of water when stored in the open.









#### **PRODUCT DATA**

Revision Date 07/20jg Page 2 of 2





# Eurosyn SFE 10w/40

Fuel Efficient Low SAPS Full Synthetic Diesel Engine Oil Product Code: A0k



Biodegradable Lubricants

## **Health & Safety**

Please refer to the relevant Health and Safety Data Sheet, a copy of which is freely available to all our customers.

Agricultural Lubricants Data represented is typical of that obtained with normal production tolerances and does not constitute a specification. The policy of Pennine Lubricants is one of continual improvement, we therefore reserve the right to change specifications without notice.



















32 Atlas Way,

Sheffield, S4 7QQ