



Industrial
Lubricants



Automotive
Lubricants



Biodegradable
Lubricants



Agricultural
Lubricants



Cleaning &
Maintenance



Greases &
Pastes



Foodsafe
Lubricants



Heritage Oils



Lubrication
Equipment



Metalworking
Fluids



Combicut FG

High Performance Neat Grinding Fluid
Product Code: AFA

Product Description

Pennine Combicut FG is a specially developed multipurpose neat cutting oil for use as a combination cutting oil, hydraulic oil and machine lubricant. Based on highly refined mineral oil it incorporates special surface active and lubricity agents as well as other performance additives to offer good inherent lubricity, and excellent surface finish.

Applications

Combicut FG is primarily recommended for use in heavy duty form grinding operations such as flute grinding of drills and taps where high wheel speeds and feed rates are used. It may also be used in light to medium duty cutting operations. Combicut FG may also be used in non-critical low pressure hydraulic systems.

Typical Test Data

| | |
|-------------------|------|
| Density @ 15°C | 0.88 |
| K.V. @ 40°C (cSt) | 31.2 |
| Flash Point (°C) | 215 |

Availability

Pennine Combicut FG is available in bulk, 1000 litre IBC's, 205 litre barrels and 25 litre drums.

Storage

Barrels of lubricant should always be stored in such a way that will prevent the ingress of water when stored in the open.

Health & Safety

Please refer to the relevant Health and Safety Data Sheet, a copy of which is freely available to all our customers.

Data represented is typical of that obtained with normal production tolerances and does not constitute a specification. The policy of Pennine Lubricants is one of continual improvement, we therefore reserve the right to change specifications without notice.



Certificate Number: 9480
ISO 9001



Pennine Lubricants Limited Company reg no. 3510091



32 Atlas Way,
Sheffield, S4 7QQ

T. 0114 285 2987
E. info@penninelubricants.co.uk
W. www.penninelubricants.co.uk