

**Section 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier****Product name:** GEARMAX SS 75W/90**Product code:** A4F**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of substance / mixture:** Lubricating oil for gearboxes.**1.3. Details of the supplier of the safety data sheet****Company name:** Pennine Lubricants Limited  
Unit 35 Limestone Cottage Lane  
Sheffield  
South Yorkshire  
S6 1NJ  
United Kingdom**Tel:** 0114 285 2987**Fax:** 0114 285 2988**Email:** info@penninelubes.plus.com**1.4. Emergency telephone number****Emergency tel:** 0114 285 2987 (Office hours only)**Section 2: Hazards identification****2.1. Classification of the substance or mixture****Classification under CLP:** This product has no classification under CLP.**2.2. Label elements****Label elements:** This product has no label elements.**2.3. Other hazards****PBT:** This product is not identified as a PBT/vPvB substance.**Section 3: Composition/information on ingredients****3.2. Mixtures****Hazardous ingredients:**

# SAFETY DATA SHEET

GEARMAX SS 75W/90

Page: 2

BLEND OF MINERAL OIL AND MULTIFUNCTIONAL ADDITIVES

| EINECS | CAS | PBT / WEL  | CLP Classification | Percent |
|--------|-----|--|--------------------|---------|
| -      | -   | Substance with a Community workplace exposure limit. | -                  | 50-70%  |

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. If persistent irritation occurs, obtain medical attention.

**Ingestion:** Wash out mouth with water.

**Inhalation:** Consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be irritation of the throat.

**Inhalation:** No symptoms.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Not applicable.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Alcohol resistant foam. Carbon dioxide. Dry chemical powder.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up to prevent the escape of liquid. Spillages may be slippery.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

[cont...]

# SAFETY DATA SHEET

GEARMAX SS 75W/90

Page: 3

## 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Bund large spills using absorbent granules, sand or earth and reclaim bulk liquid.

## 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed.

### 7.3. Specific end use(s)

**Specific end use(s):** No data available.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Hazardous ingredients:**

**BLEND OF MINERAL OIL AND MULTIFUNCTIONAL ADDITIVES**

**Workplace exposure limits:**

**Respirable dust**

| State | 8 hour TWA         | 15 min. STEL | 8 hour TWA | 15 min. STEL |
|-------|--------------------|--------------|------------|--------------|
| UK    | 5mg/m <sup>3</sup> | -            | -          | -            |

### DNEL/PNEC Values

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Respiratory protection not required.

**Hand protection:** Gloves (oil-resistant).

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Colour:** Amber

**Odour:** Characteristic odour

**Evaporation rate:** Negligible

[cont...]

# SAFETY DATA SHEET

GEARMAX SS 75W/90

Page: 4

**Solubility in water:** Insoluble

**Viscosity:** Viscous

**Kinematic viscosity:** 94

**Viscosity test method:** Kinematic Viscosity at 40C (cSt)

**Boiling point/range°C:** >200

**Flash point°C:** 220

**Relative density:** 0.865

## 9.2. Other information

**Other information:** No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

**Conditions to avoid:** Heat. Sources of ignition.

### 10.5. Incompatible materials

**Materials to avoid:** Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

**Toxicity values:** No data available.

### Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be irritation of the throat.

**Inhalation:** No symptoms.

## Section 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity values:** No data available.

[cont...]

# SAFETY DATA SHEET

GEARMAX SS 75W/90

Page: 5

## 12.2. Persistence and degradability

**Persistence and degradability:** Not readily biodegradable.

## 12.3. Bioaccumulative potential

**Bioaccumulative potential:** Bioaccumulation potential.

## 12.4. Mobility in soil

**Mobility:** Readily absorbed into soil.

## 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

## 12.6. Other adverse effects

**Other adverse effects:** Negligible ecotoxicity.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Waste code number:** 13 02 06

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

**Transport class:** This product does not require a classification for transport.

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Specific regulations:** Not applicable.

### 15.2. Chemical Safety Assessment

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

\* indicates text in the SDS which has changed since the last revision.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.