



Industrial Lubricants



Automotive Lubricants



Biodegradable Lubricants



Agricultural Lubricants



Cleaning & Maintenance



Greases & Pastes



Foodsafe Lubricants



Heritage Oils



Lubrication Equipment



Metalworking Fluids



## Fungicide MWF

Broad Spectrum Fungicide For Metalworking Fluid Emulsions

Product Code: AGW

### Product Profile

Fungicide MWF is a “tank side” secondary treatment broad spectrum fungicide for use in self-contained or centralised water-based coolant systems and machine tools using soluble metalworking fluids.

### Applications

Fungicide MWF is used to control fungal, mould and yeast infections found in water-based metalworking fluids. It helps to reduce objectionable odours emitted by metalworking fluids suffering from fungal contamination whilst not affecting the stability and performance of the fluid.

It can be used whilst the machine is in operation and thus there is no loss of production time.

The product may be used at a low level to control fungal infections in systems which are known to suffer problems. Erratic use of uncontrolled quantities is not recommended.

### Instruction For Use

When handling the product wear suitable PPE including:

- Gloves
- Safety glasses
- Face mask (if splashing may occur)

Carefully calculate the volume of coolant in the machine tool sump.

If the neat product comes into contact with skin, wash off immediately with warm water. For further information refer to relevant Safety Data Sheet.

Controlling Dose	Coolant Tank Volume x 0.2% = ml/ltr required
------------------	--

**N.B. Overdosing of Fungicide MWF may cause skin and or respiratory related issues.**



Certificate Number: 9480  
ISO 9001



Pennine Lubricants Limited Company reg no. 3510091



32 Atlas Way,  
Sheffield, S4 7QQ

T. 0114 285 2987  
E. info@penninelubricants.co.uk  
W. www.penninelubricants.co.uk



Industrial  
Lubricants



Automotive  
Lubricants



Biodegradable  
Lubricants



Agricultural  
Lubricants



Cleaning &  
Maintenance



Greases &  
Pastes



Foodsafe  
Lubricants



Heritage Oils



Lubrication  
Equipment



Metalworking  
Fluids



## Fungicide MWF

Broad Spectrum Fungicide For Metalworking Fluid Emulsions

Product Code: AGW

Physical fungal matter should be removed from the machine before the additive is added to the emulsion.

The additive should be added to the metalworking fluid at a point of high turbulence and circulated for at least 30 minutes to ensure it is thoroughly mixed into the emulsion.

Ensure that **ALL** Fungicide MWF additions are recorded for the date and amount added in order to meet HSE guidelines.

### Availability

Pennine Fungicide MWF is available in 25 litre drums and 5 litre plastic bottles.

### Storage

Barrels of lubricant should always be stored in such a way that will prevent the ingress of water when stored in the open. Protect from frost.

### Health & Safety

Please refer to the relevant Health and Safety Data Sheet, a copy of which is freely available to all our customers.

Data represented is typical of that obtained with normal production tolerances and does not constitute a specification. The policy of Pennine Lubricants is one of continual improvement; we therefore reserve the right to change specifications without notice.



Certificate Number: 9480  
ISO 9001



Pennine Lubricants Limited Company reg no. 3510091



32 Atlas Way,  
Sheffield, S4 7QQ

T. 0114 285 2987  
E. [info@penninelubricants.co.uk](mailto:info@penninelubricants.co.uk)  
W. [www.penninelubricants.co.uk](http://www.penninelubricants.co.uk)