



Industrial Lubricants



Automotive Lubricants



Biodegradable Lubricants




Agricultural Lubricants



Cleaning & Maintenance




Greases & Pastes



Foodsafe Lubricants



Heritage Oils



Lubrication Equipment



Metalworking Fluids



Metacut WP

Light to Moderate Duty Hand Applied Neat Cutting Oil
Product Code: AFK

Product Description

Pennine Metacut WP is a neat cutting oil based on highly refined mineral oil incorporating extreme pressure additives along with high performance lubricity improvers and non-staining sulphur containing esters. The light colour and low odour offer the user excellent work piece visibility along with an improved working environment.

Applications

Metacut WP is primarily recommended for reaming, tapping and drilling applications on materials such as low carbon steels including mild steel and certain grades of aluminium and may also be used for lighter hand applied applications on more difficult materials including stainless steels.

Features & Benefits

- Light coloured
 - Good EP Performance
 - Low odour
 - Light viscosity
- ~ Good work piece visibility
 - ~ Promotes improved tool life
 - ~ Improved operator acceptability
 - ~ Reduced stickiness / material pickup

Typical Test Data

Density @ 20°C	0.96
K. V. @ 40°C (cSt)	120
Flash Point (°C)	210
Pour Point (°C)	-10



Certificate Number: 9480
ISO 9001



Pennine Lubricants Limited Company reg no. 3510091



32 Atlas Way,
Sheffield, S4 7QQ

T. 0114 285 2987
E. info@penninelubricants.co.uk
W. www.penninelubricants.co.uk



Industrial Lubricants



Automotive Lubricants



Biodegradable Lubricants



Agricultural Lubricants



Cleaning & Maintenance



Greases & Pastes



Foodsafe Lubricants



Heritage Oils



Lubrication Equipment



Metalworking Fluids



Metacut WP

Light to Moderate Duty Hand Applied Neat Cutting Oil

Product Code: AFK

Availability

Pennine Metacut WP is available in 205 litre barrels, 25 litre drums, 5 litre and 1 litre plastic bottles.

Storage

Barrels of lubricant should always be stored in such a way that will prevent the ingress of water when stored in the open.

Health & Safety

Please refer to the relevant Health and Safety Data Sheet, a copy of which is freely available to all our customers.

Data represented is typical of that obtained with normal production tolerances and does not constitute a specification. The policy of Pennine Lubricants is one of continual improvement; we therefore reserve the right to change specifications without notice.



Certificate Number: 9480
ISO 9001



Pennine Lubricants Limited Company reg no. 3510091



32 Atlas Way,
Sheffield, S4 7QQ

T. 0114 285 2987
E. info@penninelubricants.co.uk
W. www.penninelubricants.co.uk