



Industrial Lubricants



Automotive Lubricants



Biodegradable Lubricants



Agricultural Lubricants



Cleaning & Maintenance



Greases & Pastes



Foodsafe Lubricants



Heritage Oils



Lubrication Equipment



Metalworking Fluids



Penstral GT 141

Low Temperature Lithium Grease
Product Code: ARB

Product Description

Pennine Penstral GT 141 is a grease specifically designed for low temperature and high speed applications. It offers excellent low temperature properties, good mechanical stability, water resistance and corrosion resistance combined with high load capacity.

Applications

For use in all types of automotive/industrial applications where low temperatures are encountered, e.g. cold stores and doors on refrigerated vehicles. It is also used in automotive, applications such as winding mechanisms and electric motors subject to wide climate conditions.

Typical Test Data

NLGI Classification	2
Colour	Yellow
Thickener	Lithium
Drop Point (°C)	180
Penetration	265-295
Operating Temperature Typical (°C)	-40 To +120

Availability

Pennine Penstral GT 141 is available in 180kg Barrels, 50kg and 12.5kg kegs, 3kg tins and 400 g cartridges.

Storage

Barrels of lubricant should always be stored in such a way that will prevent the ingress of water when stored in the open.

Health & Safety

Please refer to the relevant Health and Safety Data Sheet, a copy of which is freely available to all our customers.

Data represented is typical of that obtained with normal production tolerances and does not constitute a specification. The policy of Pennine Lubricants is one of continual improvement; we therefore reserve the right to change specifications without notice.



Certificate Number: 9480
ISO 9001



Pennine Lubricants Limited Company reg no. 3510091



32 Atlas Way,
Sheffield, S4 7QQ

T. 0114 285 2987
E. info@penninelubricants.co.uk
W. www.penninelubricants.co.uk