



Industrial
Lubricants



Automotive
Lubricants



Biodegradable
Lubricants



Agricultural
Lubricants



Cleaning &
Maintenance



Greases &
Pastes



Foodsafe
Lubricants



Heritage Oils



Lubrication
Equipment



Metalworking
Fluids



Penstral GX 286

Salt Water Resistant Heavy Duty Adhesive Grease
Product Code: ARN

Product Description

Pennine Penstral GX 286 is a premium quality semi synthetic extreme pressure grease with outstanding water resistance properties. It is primarily recommended for the lubrication of slow to medium speed plain and antifriction bearings in saturated applications in both fresh and salt water.

Applications

Penstral GX 286 is recommended for applications where a grease with exceptional water resistance is required, including marine and water utility industries, and in other industrial applications where water saturation occurs and conventional lithium-based products fail to provide adequate protection.

Typical Test Data

Worked Penetration	265-295
NLGI Classification	2
Colour	Light Green
Drop Point (°C)	185
Base Oil K. V. @ 40°C (cSt)	460
Operating Temperature Typical (°C)	-7 to 140

Availability

Pennine Penstral GX 286 is available in 180kg Barrels, 50kg and 12.5kg kegs and 400 g cartridges.

Storage

Barrels of lubricant should always be stored in such a way that will prevent the ingress of water when stored in the open.

Health & Safety

Please refer to the relevant Health and Safety Data Sheet, a copy of which is freely available to all our customers.

Data represented is typical of that obtained with normal production tolerances and does not constitute a specification. The policy of Pennine Lubricants is one of continual improvement; we therefore reserve the right to change specifications without notice.



Certificate Number: 9480
ISO 9001



Pennine Lubricants Limited Company reg no. 3510091



32 Atlas Way,
Sheffield, S4 7QQ

T. 0114 285 2987
E. info@penninelubricants.co.uk
W. www.penninelubricants.co.uk