



Industrial Lubricants



Automotive Lubricants



Biodegradable Lubricants



Agricultural Lubricants



Cleaning & Maintenance



Greases & Pastes



Foodsafe Lubricants



Heritage Oils



Lubrication Equipment



Metalworking Fluids



Red Rubber Grease

Product Code: ASH

A premium quality bio-degradable bentone thickened automotive grease for use in hydraulic systems, especially braking systems, where compatibility with natural, styrene butadiene (SBR), and other types of rubber seal is desirable. Due to the vegetable base oil, the grease is resistant to hydrocarbon solvents, notably petrol and diesel. A red dye is incorporated for identification purposes.

FEATURES

- Fully bio-degradable
- Resistant to solvents
- Good rubber compatibility
- Good corrosion protection

METHOD OF APPLICATION

RED RUBBER GREASE can be applied manually, or by using a suitable applicator. As with all greases used for the first time, check compatibility with the grease applied previously and if necessary purge bearings prior to application. Likewise, as a general rule, take care not to over-lubricate and apply the quantity of grease recommended by the bearing manufacturer.

| Properties | Specification | |
|---|---------------|-------------------------|
| Appearance | - | Smooth Grease |
| Colour | - | Red |
| NLGI classification | - | 2/3 |
| Thickener | - | Bentone |
| Base oil | - | Blend of Vegetable oils |
| Worked penetration | IP50 | 250-280 |
| Dropping point (°C) | IP132 | >260 |
| Effect on natural rubber (volume change) | - | 1% to 6% |
| Effect on Neoprene rubber (Volume change) | - | -10% to 10% |
| High Temperature Stability @120°C | - | No polymerisation |
| Operating temperature range | - | -5 to 120°C |



Certificate Number: 9480
ISO 9001



Pennine Lubricants Limited Company reg no. 3510091

32 Atlas Way,
Sheffield, S4 7QQ

T. 0114 285 2987
E. info@penninelubricants.co.uk
W. www.penninelubricants.co.uk