



Industrial
Lubricants



Automotive
Lubricants



Biodegradable
Lubricants



Agricultural
Lubricants



Cleaning &
Maintenance



Greases &
Pastes



Foodsafe
Lubricants



Heritage Oils



Lubrication
Equipment



Metalworking
Fluids



Transformer Oil B

Naphthenic Electrical Switchgear Oil
Product Code: AJM

Product Description

Pennine Transformer Oil B is a gas absorbing refined light mineral oil for electrical applications.

Applications

Used as a coolant to dissipate heat in a transformer as a dielectric to insulate electrical equipment and as an arc extinguishing agent.

Performance Specifications

Pennine Transformer Oil B meets the requirements of the following specifications :-

BS148 1984 Type 1

IEC 296 1982 Class 1

SEV 3163 1972 Class 1

Typical Test Data

Density @ 20°C	0.89
K.V. @ 40°C (cSt)	12-14
K.V. @ 100°C (cSt)	3
Flash Point (°C)	140
Pour Point (°C)	-30

Availability

Pennine Transformer Oil B is available in 1000 litre IBC's, 205 litre barrels and 25 litre drums.

Storage

Barrels of lubricant should always be stored in such a way that will prevent the ingress of water when stored in the open.

Health and Safety

Please refer to the relevant Health and Safety Data Sheet, a copy of which is freely available to all our customers.

Data represented is typical of that obtained with normal production tolerances and does not constitute a specification. The policy of Pennine lubricants is one of continual improvement, we therefore reserve the right to change specifications without notice.



Certificate Number: 9480
ISO 9001



Pennine Lubricants Limited Company reg no. 3510091



32 Atlas Way,
Sheffield, S4 7QQ

T. 0114 285 2987
E. info@penninelubricants.co.uk
W. www.penninelubricants.co.uk