

Section 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier****Product name:** ULTRASOL X-NF**Product code:** AWF**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of substance / mixture:** PC25: Metal working fluids.**1.3. Details of the supplier of the safety data sheet****Company name:** Pennine Lubricants Limited

Unit 35 Limestone Cottage Lane

Sheffield

South Yorkshire

S6 1NJ

United Kingdom

Tel: 0114 285 2987**Fax:** 0114 285 2988**Email:** info@penninelubes.plus.com**1.4. Emergency telephone number****Emergency tel:** 0114 285 2987 (Office hours only)**Section 2: Hazards identification****2.1. Classification of the substance or mixture****Classification under CLP:** Aquatic Chronic 3: H412; Eye Irrit. 2: H319**Most important adverse effects:** Causes serious eye irritation. Harmful to aquatic life with long lasting effects.**2.2. Label elements****Label elements:****Hazard statements:** H319: Causes serious eye irritation.

H412: Harmful to aquatic life with long lasting effects.

Hazard pictograms: GHS07: Exclamation mark**Signal words:** Warning**Precautionary statements:** P264: Wash hands thoroughly after handling.

P273: Avoid release to the environment.

SAFETY DATA SHEET

ULTRASOL X-NF

Page: 2

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+313: If eye irritation persists: Get medical attention.

P501: Dispose of contents/container to hazardous or special waste collection point.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

SULPHONIC ACIDS, PETROLEUM, SODIUM SALTS - REACH registered number(s): 01-2119527859-22-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
271-781-5	68608-26-4	-	Eye Irrit. 2: H319	10-30%

N-(3-AMINOPROPYL)-N-DODECYLPROPANE-1,3-DIAMINE

219-145-8	2372-82-9	-	STOT RE 2: H373; Aquatic Acute 1: H400; Skin Corr. 1B: H314; Aquatic Chronic 1: H410; Acute Tox. 3: H301	<1%
-----------	-----------	---	--	-----

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. For contact with undiluted fluid, obtain prompt medical attention.

Ingestion: Do not induce vomiting. Wash out mouth with water. If aspiration is suspected, obtain immediate medical attention.

Inhalation: Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

[cont...]

SAFETY DATA SHEET

ULTRASOL X-NF

Page: 3

5.1. Extinguishing media

Extinguishing media: Carbon dioxide. Alcohol resistant foam. Dry chemical powder.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Spillages may be slippery. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Bund large spills using absorbent granules, sand or earth and reclaim bulk liquid.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): PC25: Metal working fluids.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

[cont...]

SAFETY DATA SHEET

ULTRASOL X-NF

Page: 4

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Gloves (oil-resistant).

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Brown

Odour: Barely perceptible odour

Evaporation rate: Negligible

Solubility in water: Miscible

Viscosity: Viscous

Kinematic viscosity: 50-100

Viscosity test method: Kinematic Viscosity at 40C (cSt)

Boiling point/range°C: >100

Flash point°C: >100

Relative density: 0.91

pH: 8.8-9

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid: Extremes of temperature, store between 0 and 40C

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

[cont...]

SAFETY DATA SHEET

ULTRASOL X-NF

Page: 5

11.1. Information on toxicological effects

Relevant hazards for product:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Inherently biodegradable

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: No data available.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Waste code number: 12 01 07

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

[cont...]

SAFETY DATA SHEET

ULTRASOL X-NF

Page: 6

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H301: Toxic if swallowed.

H314: Causes severe skin burns and eye damage.

H319: Causes serious eye irritation.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.