

Version: 1.0 EU/EN

Revision: 15/01/2022

Page: 1 of 11

**SAFETY DATA SHEET**  
ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),  
1272/2008 (CLP) & 2015/830

**Ultrasol X-NT 736**

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

**1.1 Product identifier**

**Ultrasol X-NT 736**

Synonym(s):	None
REACH Registration No.:	Not applicable - Mixture
EC No.:	Not applicable - Mixture
EC INDEX No.:	Not applicable - Mixture
CAS No.:	Not applicable - Mixture

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Identified Use(s): Metalworking fluid - soluble. To be diluted in water prior to use.  
For specific application advice see appropriate Technical Data Sheet or consult our company representative.

Uses Advised Against: This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier.

**1.3 Details of the supplier of the safety data sheet**

Company Address	Pennine Lubricants Ltd 32 Atlas way Sheffield, S4 7QQ
Telephone:	+44(0)114 285 2987
E-mail:	<a href="mailto:info@penninelubricants.co.uk">info@penninelubricants.co.uk</a>

**1.4 Emergency telephone number**

+44(0)114285297                      0900 - 17.00 Monday - Friday

**SECTION 2: HAZARDS IDENTIFICATION**

**2.1 Classification of the substance or mixture**

According to Regulation (EC) No. 1272/2008 (CLP):	Skin corrosion/irritation - Category 2. H315: Causes skin irritation. Serious eye damage/irritation - Category 1. H318: Causes serious eye damage. Hazardous to the aquatic environment: Aquatic Chronic - Category 3. H412: Harmful to aquatic life with long lasting effects.
---	---

**2.2 Label elements**

Hazard Pictogram(s):



Signal Word(s): Danger

Hazard Statement(s): H315: Causes skin irritation.  
H318: Causes serious eye damage.  
H412: Harmful to aquatic life with long lasting effects.

Precautionary Statement(s):

**Prevention:**  
P273: Avoid release to the environment.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.

**Response:**  
P302+P352: IF ON SKIN: Wash with plenty of water.  
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310: Immediately call a POISON CENTER/doctor.  
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.  
P391: Collect spillage.

**Storage:**  
No precautionary phrases.

**Disposal:**  
P501: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Version: 1.0 EU/EN

Revision: 15/01/2022

Page: 2 of 11

**SAFETY DATA SHEET**  
ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),  
1272/2008 (CLP) & 2015/830

**Ultrasol X-NT 736**

Supplemental label elements: None.

**2.3 Other hazards**

Other hazards which do not result in classification:

May cause allergic reaction in susceptible people.  
Repeated and/or prolonged skin contact with in-use emulsions, especially if over-strength, may lead to defatting of the skin.

PBT / vPvB:

Material does not meet the criteria for PBT or vPvB in accordance with REACH Annex XIII.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

**3.2 Mixtures**

This material is a mixture.

Chemical nature:

Highly refined mineral oil, emulsifiers and corrosion inhibitors with other additives. To be diluted in water prior to use.  
The highly refined mineral oil contains <3% (w/w) DMSO extract, according to IP346.

**Hazardous Ingredient(s)**

Chemical Name	Identifiers	%	Classification (According to Regulation (EC) No. 1272/2008 (CLP))
2,2'-Iminodiethanol	CAS: 111-42-2 EC No.: 203-868-0 EC INDEX No.: 603-071-00-1 REACH: 01-2119488930-28	1 - 9.99	Acute Tox. 4 (Oral); H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT RE 2; H373
2-phenoxythanol	CAS: 122-99-6 EC No.: 204-589-7 EC INDEX No.: 603-098-00-9 REACH: 01-2119488943-21	1 - 9.99	Acute Tox. 4 (Oral); H302 Eye Irrit. 2; H319
Polycarboxylic acid neutralised with alkyiltriamine**	CAS: Not available EC No.: Not available REACH: Equilibrium of ionic pairs**	1 - 9.99	Acute Tox. 4 (Dermal); H312 Skin Irrit. 2; H315 Eye Dam. 1; H318 Aquatic Chronic 3; H412
Alkyl ether carboxylic acids neutralised with 2,2'-Iminodiethanol**	CAS: Not available EC No.: Polymer REACH: Equilibrium of ionic pairs**	1 - 9.99	Skin Irrit. 2; H315 Eye Dam. 1; H318
Phosphate ester neutralised with alkyiltriamine**	CAS: Not available EC No.: Polymer REACH: Equilibrium of ionic pairs**	1 - 9.99	Acute Tox. 4 (Oral); H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Aquatic Chronic 3; H412
Alcohols, C11-14-iso-, C13-rich	CAS: 68526-86-3 EC No.: 271-235-6 REACH: 01-2119454259-32	1 - 4.99	Skin Irrit. 2; H315 Aquatic Acute 1; H400 Aquatic Chronic 2; H411
Alcohols, C9-11, ethoxylated	CAS: 68439-46-3 EC No.: Polymer REACH: Polymer	1 - 4.99	Eye Dam. 1; H318
Pyridine-2-thiol 1-oxide, sodium salt	CAS: 3811-73-2 EC No.: 223-296-5 REACH: BPR Review program substance	<1	Acute Tox. 4 (Oral); H302 Acute Tox. 4 (Inhalation); H332 Acute Tox. 3 (Dermal); H311 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Aquatic Acute 1; H400 (M=100) Aquatic Chronic 1; H410 (M=10)

\*\* Neutralisation product: Equilibrium of ionic pairs in aqueous solution according to REACH, Annex V, 4.

See Section 16 for the full text of the H statements declared above.

**SECTION 4: FIRST AID MEASURES**

**4.1 Description of first aid measures**

Eye Contact:

Immediately flush eyes for at least 15 minutes. Irrigate eyes thoroughly whilst lifting eyelids. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention.

Version: 1.0 EU/EN

Revision: 15/01/2022

Page: 3 of 11

**SAFETY DATA SHEET**  
ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),  
1272/2008 (CLP) & 2015/830

**Ultrasol X-NT 736**

Skin Contact:	Wash skin with soap and water. Remove contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
Ingestion:	Do NOT induce vomiting. Provided the patient is conscious, wash out mouth with water and give 200-300 ml (half a pint) of water to drink. Never give anything by mouth to an unconscious person. Get medical attention.
Inhalation:	IF INHALED: Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. If breathing is laboured, administer oxygen. Seek medical treatment when anyone has symptoms apparently due to inhalation. The effect of inhalation may be delayed.
<b>4.2 Most important symptoms and effects, both acute and delayed</b>	
Eye Contact:	Causes severe irritation. May cause corneal damage. In-use dilute emulsions may cause transient irritation.
Skin Contact:	May cause irritation. May cause allergic reaction in susceptible people. Repeated and/or prolonged skin contact with in-use emulsions, especially if over-strength, may lead to defatting of the skin.
Ingestion:	The ingestion of significant quantities may cause nausea/vomiting. Abdominal pain. The ingestion of significant quantities may cause damage to digestive system.
Inhalation:	Unlikely to be hazardous by inhalation because of the low vapour pressure of the material at ambient temperature. Vapours or fumes evolved during thermal processing may cause irritation to the respiratory system.
<b>4.3 Indication of any immediate medical attention and special treatment needed</b>	Treat symptomatically.

**SECTION 5: FIREFIGHTING MEASURES**

<b>5.1 Extinguishing media</b>	
Suitable extinguishing media:	Extinguish preferably with dry chemical, sand, foam or carbon dioxide.
Unsuitable extinguishing media:	Do not use water jet.
<b>5.2 Special hazards arising from the substance or mixture</b>	
Combustion products:	May give off toxic fumes in a fire. Combustion products may include the following: Oxides of carbon; Sulphur oxides; oxides of phosphorus; Nitrogen oxides; Incomplete combustion products; Toxic gases/vapours.
<b>5.3 Advice for firefighters</b>	
Special protective equipment and precautions for fire fighters:	Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Water spray should be used to cool containers.
<b>5.4 Additional Information</b>	Dispose of contaminated extinction water according to official regulations. Prevent liquid entering watercourses and sewers.

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

<b>6.1 Personal precautions, protective equipment and emergency procedures</b>	
	Avoid generation of mist. Avoid breathing mist/vapours/spray. Spillage causes slippery surface. Clean up spill immediately. Wear suitable protective clothing. See Also Section 8.
<b>6.2 Environmental precautions</b>	Contain spillages. Prevent release to the environment. Prevent entry into drains. Disposal should be in accordance with local, state or national legislation. See Also Section 13.
<b>6.3 Methods and material for containment and cleaning up</b>	
Small spillages:	Stop leak if safe to do so. Absorb spillage in suitable inert material. Collect as much as possible in clean container for reuse or disposal. Seal containers and label them.

## Ultrasol X-NT 736

Large spillages:

Stop leak if safe to do so. Contain spillages. Prevent release to the environment. Dyke to prevent entry to sewer or waterway. Transfer liquid to a holding container. Absorb remaining liquid in sand or inert absorbent and remove to safe place. Seal containers and label them. Disposal should be in accordance with local, state or national legislation.

**6.4 Reference to other sections**

For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet.

### SECTION 7: HANDLING AND STORAGE

**7.1 Precautions for safe handling**

Avoid contact with skin and eyes. Wear suitable gloves and eye/face protection. Avoid breathing mist/vapours/spray. Provide adequate ventilation, including appropriate local extraction if fumes or vapours are likely to be evolved. Do not eat, drink or smoke when using this product.

**7.2 Conditions for safe storage, including any incompatibilities**

Keep containers in a clean, cool and dry area away from heat sources. Protect from frost. Keep away from direct sunlight. Keep container tightly closed and in a well-ventilated place.

**7.3 Specific end use(s)**

Metalworking fluid - soluble. Contact supplier for further information.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

**8.1 Control parameters**

Occupational Exposure Limits:

IOELV: Indicative Occupational Exposure Limit Value: None assigned.

Other Occupational Exposure Limits. (Information on ingredients)

Chemical Name	%	LTEL (8hr TWA)	STEL	Source
Mineral oil	40-60	5 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	TLV (ACGIH)
		5 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	PEL (OSHA)

Recommended monitoring method:

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

PNECs and DNELs:

Information on ingredients - DNEL

Chemical Name	exposure	population potentially exposed	Exposure route	
<b>2-phenoxyethanol</b>				
20.83 mg/kg Body weight /day	Chronic	Workers	Dermal	Systemic effects
8.07 mg/m <sup>3</sup>	Chronic	Workers	Inhalation	Systemic effects
8.07 mg/m <sup>3</sup>	Chronic	Workers	Inhalation	Local effects
10.42 mg/kg Body weight /day	Chronic	Consumers	Dermal	Systemic effects
2.41 mg/m <sup>3</sup>	Chronic	Consumers	Inhalation	Systemic effects
2.41 mg/m <sup>3</sup>	Chronic	Consumers	Inhalation	Local effects
<b>2,2'-Iminodiethanol</b>				
0.13 mg/kg Body weight /day	Chronic	Workers	Dermal	Systemic effects

Version: 1.0 EU/EN

Revision: 15/01/2022

Page: 5 of 11

**SAFETY DATA SHEET**  
ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),  
1272/2008 (CLP) & 2015/830

**Ultrasol X-NT 736**

0.75 mg/m <sup>3</sup>	Chronic	Workers	Inhalation	Systemic effects
0.5 mg/m <sup>3</sup>	Chronic	Workers	Inhalation	Local effects
0.07 mg/kg Body weight /day	Chronic	Consumers	Dermal	Systemic effects
0.125 mg/m <sup>3</sup>	Chronic	Consumers	Inhalation	Systemic effects
0.125 mg/m <sup>3</sup>	Chronic	Consumers	Inhalation	Local effects

Information on ingredients - PNEC

2-phenoxyethanol		
Aquatic Compartment	Fresh water	0.943 mg/l
	Sea water	0.094 mg/l
Microbiological Activity in Sewage Treatment Systems		24.8 mg/l
Sediment Compartment	Fresh water	7.237 mg/kg
	Sea water	0.724 mg/kg
Terrestrial Compartment	Soil	1.26 mg/kg
2,2'-Iminodiethanol		
Aquatic Compartment	Fresh water	0.021 mg/l
	Sea water	0.002 mg/l
Microbiological Activity in Sewage Treatment Systems		100 mg/l
Sediment Compartment	Fresh water	0.092 mg/kg
	Sea water	0.009 mg/kg
Terrestrial Compartment	Soil	1.63 mg/kg

**8.2 Exposure controls**

Engineering controls:

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Provide adequate ventilation, including appropriate local extraction if dusts, fumes or vapours are likely to be evolved. Engineering controls should be provided which maintain airborne concentrations below the relevant guidelines. The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances.

Occupational exposure controls:

No special requirements. Provide adequate ventilation if fumes or vapours are likely to be evolved to ensure that the defined occupational exposure limit is not exceeded.

Personal protection equipment:

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye/ face protection:

Wear eye protection with side protection (EN166).

Hand protection:

Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity.

Breakthrough time of the glove material: refer to the information provided by the gloves' producer.

For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.

Always seek advice from glove suppliers.

Body protection:

Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin.

Version: 1.0 EU/EN

Revision: 15/01/2022

Page: 6 of 11

**SAFETY DATA SHEET**  
ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),  
1272/2008 (CLP) & 2015/830

**Ultrasol X-NT 736**

Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Respiratory protection:

No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapours Type A/Type P boiling point > 65°C (149°F) meeting EN14387 and EN143.

Environmental exposure controls:

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

Appearance	Dark. Amber. Liquid
Odour	Characteristic.
Odour threshold	Not available.
pH	~9.8 - ~9.45 @ 5% dilution in water.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	>100 °C [Closed cup]
Evaporation rate	Not available.
Flammability	Not available.
Upper/lower flammability or explosive limits	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	0.965 @ 15°C
Solubility(ies)	Emulsifies in water.
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature	Not available.
Decomposition Temperature	Not available.
Viscosity	>48 mm <sup>2</sup> /s @ 40°C
Explosive properties	Not explosive
Oxidising properties	Not oxidising

### 9.2 Other information

No information available.

## SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity

Stable. No specific test data available for this product.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose.

### 10.4 Conditions to avoid

Should be kept away from naked flames and other sources of ignition.

## Ultrasol X-NT 736

- 10.5 Incompatible materials** May react with strong acids or strong oxidizing agents, such as chlorates, nitrates, peroxides, etc
- 10.6 Hazardous decomposition products** No hazard expected under normal conditions of use. Combustion or thermal decomposition will evolve toxic and irritant vapours. Decomposition products may include carbon oxides.; Sulphur oxides; oxides of phosphorus; Nitrogen oxides; Incomplete combustion products;

### SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1 Information on toxicological effects

**Acute toxicity:**

No specific test data available for this product. Low toxicity expected under normal conditions of use. Based upon the available data, the classification criteria are not met. (Based on assessment of the components.)

Information on ingredients:-

Chemical Name	Value
2-phenoxyethanol	LD50 (oral) mg/kg: 1850 (rat) LD50 (dermal) mg/kg: >5000 (rabbit)
2,2'-Iminodiethanol	LD50 (oral) mg/kg: ~1600 (rat) LD50 (dermal) mg/kg: 12200 (rabbit)
Alcohols, C9-11, ethoxylated	(By analogy with similar materials) LD50 (oral) mg/kg: 3488 (rat) LD50 (dermal) mg/kg: >2000 (rabbit)
Alcohols, C11-14-iso-, C13-rich	LD50 (oral) mg/kg: >2000 (rat) LD50 (dermal) mg/kg: >2000 (rabbit)
Pyridine-2-thiol 1-oxide, sodium salt	LD50 (oral) mg/kg: 750 (rat) (calculated) LD50 (dermal) mg/kg: 700 (rabbit) (calculated)

**Skin corrosion/irritation:**

No specific test data available for this product. May cause irritation (Based on assessment of the components.)

Information on ingredients:-

Chemical Name	Value
2-phenoxyethanol	Non-irritant (rabbit)
2,2'-Iminodiethanol	Irritant (rabbit)
Alcohols, C9-11, ethoxylated	Non-irritant (rabbit) (By analogy with similar materials)
Alcohols, C11-14-iso-, C13-rich	Irritant (rabbit)
Pyridine-2-thiol 1-oxide, sodium salt	Irritant (rabbit)

**Serious eye damage/irritation:**

No specific test data available for this product. Causes severe eye irritation. May cause corneal damage. (Based on assessment of the components.)

Information on ingredients:-

Chemical Name	Value
2-phenoxyethanol	Irritant (rabbit)
2,2'-Iminodiethanol	Corrosive (rabbit)
Alcohols, C9-11, ethoxylated	Severe irritant (rabbit) (By analogy with similar materials)
Alcohols, C11-14-iso-, C13-rich	Non-irritant (rabbit)
Pyridine-2-thiol 1-oxide, sodium salt	Irritant (rabbit)

**Respiratory or skin sensitisation:**

No specific test data available for this product. May cause allergic reaction in susceptible people. (Based on assessment of the components.)

Information on ingredients:-

Version: 1.0 EU/EN

Revision: 15/01/2022

Page: 8 of 11

**SAFETY DATA SHEET**  
ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),  
1272/2008 (CLP) & 2015/830

**Ultrasol X-NT 736**

Chemical Name	Value
2-phenoxyethanol	Sensitisation (guinea pig) - Negative
2,2'-Iminodiethanol	Sensitisation (guinea pig) - Negative
Alcohols, C9-11, ethoxylated	Sensitisation (guinea pig) - Negative (By analogy with similar materials)
Alcohols, C11-14-iso-, C13-rich	Sensitisation (guinea pig) - Negative (By analogy with similar materials)
Pyridine-2-thiol 1-oxide, sodium salt	Sensitisation (guinea pig) - Negative

Germ cell mutagenicity:

No specific test data available for this product. Based upon the available data, the classification criteria are not met. (Based on assessment of the components.)

Information on ingredients:-

Chemical Name	Value
2-phenoxyethanol	Negative
2,2'-Iminodiethanol	Negative (OECD 471)
Alcohols, C9-11, ethoxylated	Negative (By analogy with similar materials)
Alcohols, C11-14-iso-, C13-rich	Negative (By analogy with similar materials)

Carcinogenicity:

IARC, NTP, OSHA, ACGIH do not list this product or any components thereof as known or suspected carcinogen.

Reproductive toxicity:

No specific test data available for this product. Based upon the available data, the classification criteria are not met. (Based on assessment of the components.)

Information on ingredients:-

Chemical Name	Value
2-phenoxyethanol	NOAEL 375 mg/kg/day (rat)
2,2'-Iminodiethanol	NOAEL 100 mg/kg/day (OECD 443 (rat))
Pyridine-2-thiol 1-oxide, sodium salt	NOAEL 3.5 mg/kg/day (EPA US EPA 83-4/OECD 416 (rat))

Specific target organ toxicity — single exposure:

No specific test data available for this product. No known significant effects or critical hazards (Based on assessment of the components.)

Specific target organ toxicity — repeated exposure:

No specific test data available for this product. Based upon the available data, the classification criteria are not met. (Based on assessment of the components.)

Information on ingredients:-

Chemical Name	Value
2,2'-Iminodiethanol	<b>Repeated dose toxicity: via oral route - systemic effects (target organ)</b> cardiovascular / hematological: other; urogenital: kidneys <b>Repeated dose toxicity: inhalation - systemic effects (target organ)</b> respiratory: larynx <b>Repeated dose toxicity: dermal - systemic effects (target organ)</b> cardiovascular / hematological: other; digestive: liver; urogenital: kidneys; other: skin

Aspiration hazard:

No specific test data available for this product. Based upon the available data, the classification criteria are not met. (Based on physico-chemical properties of the material.)

Additional Information:

No information available.

## Ultrasol X-NT 736

### SECTION 12: ECOLOGICAL INFORMATION

#### 12.1 Toxicity

No specific test data available for this product. May cause long lasting harmful effects to aquatic life. (Based on assessment of the components.)

Information on ingredients:-

Chemical Name	Value
2-phenoxyethanol	344 mg/l LC50 (96 hour) (Pimephales promelas) >500 mg/l EC50 (48 hour) (Daphnia magna) > 500 mg/l EC50 (72 hour) (Desmodesmus subspicatus)
2,2'-Iminodiethanol	23 mg/l NOEC (34 days) (Pimephales promelas) 9.433 mg/l NOEC (21 days) (Daphnia magna)
2,2'-Iminodiethanol	460 mg/l LC50, (96 hour) (Oncorhynchus mykiss) 30.1 mg/l EC50, (48 hour) (Ceriodaphnia dubia) 9.5 mg/l EC50, (72 hour) (Selenastrum capricornutum)
Alcohols, C9-11, ethoxylated	1.05 mg/l EC10, (21 days) (Daphnia magna) (By analogy with similar materials) 5 - 7 mg/l LC50 (96 hour) (Oncorhynchus mykiss) 2.5 mg/l EC50 (48 hour) (Daphnia magna) 1.4 mg/l EC50 (72 hour) (Selenastrum capricornutum)
Alcohols, C11-14-iso-, C13-rich	0.42 mg/l LC50 (96 hour) (Oncorhynchus mykiss) 0.71 mg/l EC50 (48 hour) (Daphnia magna) 3.2 mg/l EC50 (72 hour) (Pseudokirchneriella subcapitata)
Pyridine-2-thiol 1-oxide, sodium salt	0.00264 mg/l LC50 (96 hour) (Oncorhynchus mykiss) (calculated) 0.0088 mg/l EC50 (48 hour) (Daphnia magna) (calculated) 0.0012 mg/l EC50 (120 hour) (Skeletonema costatum) (By analogy with similar materials)

#### 12.2 Persistence and degradability

No specific test data available for this product. Expected to be not readily biodegradable. Part of the components are poorly biodegradable.

Information on ingredients:-

Chemical Name	Value
2-phenoxyethanol	>90%, 15 days (Biodegradability)
2,2'-Iminodiethanol	93%, 28 days (Biodegradability)
Alcohols, C9-11, ethoxylated	(By analogy with similar materials): 72 - 100% (Biodegradability)
Alcohols, C11-14-iso-, C13-rich	61%, 28 days (Biodegradability)
Pyridine-2-thiol 1-oxide, sodium salt	Readily biodegradable
Highly refined mineral oil	2 - 31%, 28 days (Biodegradability)

#### 12.3 Bioaccumulative potential

No specific test data available for this product.

Information on ingredients:-

Chemical Name	Value
2-phenoxyethanol	0.349 (Bioconcentration factor (BCF)) (Calculated)

#### 12.4 Mobility in soil

No specific test data available for this product. Large volumes may penetrate soil and contaminate groundwater.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB.

#### 12.6 Other adverse effects

No information available.

### SECTION 13: DISPOSAL CONSIDERATIONS

#### 13.1 Waste treatment methods

Product:

Dispose of via an authorised person/ licensed waste disposal contractor in

Version: 1.0 EU/EN

Revision: 15/01/2022

Page: 10 of 11

**SAFETY DATA SHEET**  
ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),  
1272/2008 (CLP) & 2015/830

**Ultrasol X-NT 736**

accordance with local regulations. Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. This material is considered as hazardous waste pursuant to Directive 91/689/EEC on hazardous waste, and subject to the provisions of that Directive unless Article 1(5) of that Directive applies. Classification of waste is always the responsibility of the end user.

Packaging waste:

This material and its container must be disposed of in a safe way. Dispose of this material and its container as hazardous waste. Empty containers or liners may retain some product residues. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.

**SECTION 14: TRANSPORT INFORMATION**

		ADR/RID	AND/ADNR	IMDG	IATA
		Not classified as dangerous for transport.			
14.1	UN number	None	None	None	None
14.2	UN proper shipping name	Not applicable	Not applicable	Not applicable	Not applicable
14.3	Transport hazard class(es)	Not applicable	Not applicable	Not applicable	Not applicable
14.4	Packing group	Not applicable	Not applicable	Not applicable	Not applicable
14.5	Environmental hazards	Not applicable	Not applicable	Not applicable	Not applicable
14.6	Special precautions for user	No information available.	No information available.	No information available.	No information available.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code  
Not applicable.

**SECTION 15: REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

EU Regulation (EC) No. 1907/2006 (REACH): REACH Status: The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH.

REACH: ANNEX XIV list of substances subject to authorisation: Not listed

Candidate List of Substances of Very High Concern for Authorisation: Not listed

REACH: Annex XVII Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles: Not applicable

15.2 Chemical Safety Assessment A REACH chemical safety assessment has not been carried out.

**SECTION 16: OTHER INFORMATION**

The following sections contain revisions or new statements: Original safety data sheet - no previous versions

Classification procedure Calculation method. Based on assessment of the components.

Full text of abbreviated H statements H302: Harmful if swallowed.

Version: 1.0 EU/EN

Revision: 15/01/2022

Page: 11 of 11

# SAFETY DATA SHEET

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),  
1272/2008 (CLP) & 2015/830

## Ultrasol X-NT 736

---

H312: Harmful in contact with skin.  
H315: Causes skin irritation.  
H317: May cause an allergic skin reaction.  
H318: Causes serious eye damage.  
H319: Causes serious eye irritation.  
H331: Toxic if inhaled.  
H372: Causes damage to organs through prolonged or repeated exposure.  
H373: May cause damage to organs through prolonged or repeated exposure.  
H400: Very toxic to aquatic life.  
H410: Very toxic to aquatic life with long lasting effects.  
H411: Toxic to aquatic life with long lasting effects.  
H412: Harmful to aquatic life with long lasting effects.

### Abbreviations and Acronyms

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road  
CAS: Chemical Abstracts Service  
DNEL: Derived No Effect Level  
IATA: International Air Transport Association  
IBC: Intermediate Bulk Container  
IMDG: International Maritime Dangerous Goods  
LogPow: logarithm of the octanol/water partition coefficient  
MARPOL: International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. (Marpol = marine pollution)  
PBT: Persistent, Bioaccumulative and Toxic  
PNEC: Predicted No Effect Concentration  
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail  
UN: United Nations  
VPvB: very Persistent and very Bioaccumulative

*The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. The data and advice given apply when the product is sold for the stated application or applications. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations.*